

KD-400 POWERED MONITORS



ROOM-FILLING
SOUND IN YOUR HOME



SIMPLE
SET UP



DESIGNED AND
ENGINEERED IN THE USA



EASILY ADD
A SUBWOOFER



LEGENDARY, HORN-LOADED DETAILED AND
DYNAMIC KLIPSCH SOUND SINCE 1946

SIMPLE SETUP

The KD-400 powered monitors feature contemporary materials in compact wireless cabinets with integrated power for a simple yet powerful sound experience. The KD-400 is ready to play, right out of the box. The built-in amplifier with Bluetooth, analog, digital optical inputs and a subwoofer output provide simple connections for a plug-n-play experience

SMALL CABINET, BIG SOUND

The compact cabinets allow for extremely versatile placement options while treating the listener to dynamic, true-to-life audio reproduction. The KD-400 is specifically designed to provide exceptional output and balanced, full sound in any application despite its small size. .

DHORM TWEETER TECHNOLOGY

This unique Dhorm tweeter combines the benefits of a horn and dome design. What you get is smooth high frequency response, wide dynamic range and low distortion. To provide greater reliability and power handling capability, the tweeter uses a unique cooling system, giving you increased output, power handling and dynamic range.

HIGH EFFICIENCY, LOW DISTORTION

Klipsch speakers are highly efficient and designed to produce more output using less energy. The detailed, accurate sound provides hours of listening pleasure.

ADD A SUBWOOFER

Complete your system with your favorite Klipsch subwoofer.

DESIGNED AND ENGINEERED IN THE USA

Every new speaker that has the Klipsch logo bestowed upon it is designed and engineered with pride at our worldwide headquarters in Indianapolis. The team of engineers put their heart and soul into each and every Klipsch product, whether it be the smallest in-ear headphone or the biggest floorstanding speaker.

SPECIFICATIONS

FREQUENCY RESPONSE	69Hz - 23KHz -3dB
TOTAL SYSTEM POWER	48W Total System Power (96W Peak) 24W per channel cont. @ $\leq 1\%$ THD
HIGH FREQUENCY DRIVER	25mm (1") Soft Dome Tweeter
LOW FREQUENCY DRIVER	102mm (4") IMG Woofer
CROSSOVER	1800 Hz (Passive)
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via Front Firing Slot Port
INPUTS	Bluetooth® wireless technology RCA Line In Optical digital
OUTPUT	Single RCA line level output for subwoofer
VOLTAGE	100-240V 50/60Hz External power supply
DIMENSIONS (HXWXD)	270mm x 152.4mm x 174.7mm 10.63" x 6" x 6.88"
WEIGHT	10.7 lb (4.85 kg)