

## KD-52F

### FLOORSTANDING SPEAKER



#### ROOM FILLING THEATER SOUND

Delivering an incredible sound experience in an elegant package, the KD Series speakers provide soaring highs and booming lows while complementing your home décor. We put 75 years of acoustic technology into our award-winning home theater systems to give you an intense, cinematic experience every time you watch a movie or listen to music.

#### HIGH EFFICIENCY, LOW DISTORTION

Klipsch speakers are highly efficient and designed to produce more output using less energy. The detailed, accurate sound provides hours of listening pleasure.

#### DHORM TWEETER TECHNOLOGY

This unique Dhorm tweeter combines the benefits of a horn and dome design. What you get is smooth high frequency response, wide dynamic range and low distortion. To provide greater reliability and power handling capability, the tweeter uses a unique cooling system, giving you increased output, power handling and dynamic range.

#### SLEEK, CONTEMPORARY APPEARANCE

Stylish aesthetic with absolute durability that results in a seamless integration into any décor. The high-quality cabinet using the same design methods are our professional movie theater speakers, reducing vibration for a crisp, clear sound.

#### DESIGNED AND ENGINEERED IN THE USA

Every new speaker that has the Klipsch logo bestowed upon it is designed and engineered with pride at our worldwide headquarters in Indianapolis. The team of engineers put their heart and soul into each and every Klipsch product, whether it be the smallest in-ear headphone or the biggest floorstanding speaker.

#### SPECIFICATIONS

|                                   |   |
|-----------------------------------|---|
| <b>FREQUENCY RESPONSE</b>         | 42Hz - 26kHz                                    |
| <b>SENSITIVITY</b>                | 90dB (2.83V @ 1m)                               |
| <b>POWER HANDLING (CONT/PEAK)</b> | 100W / 200W                                     |
| <b>NOMINAL IMPEDANCE</b>          | 8 Ohm   |
| <b>HIGH FREQUENCY DRIVER</b>      | 25mm (1") Dhorm Tweeter                         |
| <b>LOW FREQUENCY DRIVER</b>       | 2 x 127mm (5") Polyfiber Woofers                |
| <b>CROSSOVER</b>                  | 2kHz  |
| <b>ENCLOSURE MATERIAL</b>         | MDF   |
| <b>ENCLOSURE TYPE</b>             | Bass Reflex via Front Firing Slot Port          |
| <b>INPUTS</b>                     | Single Binding Posts                            |
| <b>FINISH</b>                     | Black   |
| <b>DIMENSIONS (HXWXD)</b>         | 915mm x 191mm x 252mm<br>36.02" x 7.52" x 9.92" |
| <b>WEIGHT</b>                     | 26 lb (11.8 kg)                                 |