

IC 408 LCR FG II

2-WAY IN-CEILING SPEAKER



SPECIFICATIONS

WOOFER (mm / in)	203 / 8
MIDRANGE (mm / in)	38 / 1½
TWEETER (mm / in)	25 / 1 DTT
POWER (W LONG / SHORT TERM)	80 / 160
FREQUENCY RANGE (Hz)	55 – 22,000
IMPEDANCE (Ohm)	4 – 8 switchable
HOLE DIMENSION HxWxD (mm / in)	Ø244 x 126 / Ø9.6 x 5.0
DIMENSIONS HxWxD (mm / in)	Ø272 x 141 / Ø10.7 x 5.6
BACK BOX SIZE (Litre / in³)	22 / 1340
WEIGHT	2.4 / 5.3
FINISH	White (paintable)

ALL NEW PURE WHITE GRILLE

Redesigned magnetic, paintable grille with a new, more natural white color blends more seamlessly into the most premium of interior décor.

HIGH PERFORMANCE FRONT STAGE

Specially designed for front and center channels in a first-class home theater system, the angled tweeter and midrange design provides great clarity and detail for dialogue and effects in movies. The speaker can also be used in a premium 2-channel stereo system.

PREMIUM ACOUSTIC TECHNOLOGY

The 8" woven synthetic fiber woofer, angled 1.5" titanium dome midrange and angled 1" titanium dome tweeter provide balanced, dynamic, rich sound for your music and movies by utilizing core Jamo technologies:

- Decoupled Tweeter Technology (DTT) minimizes vibration transfer from the baffle to the tweeter, for detailed, clear high frequencies.
- WaveGuide provides focused, dynamic transfer of high frequencies into the listening space.
- Hard Conical Cone (HCC) minimizes woofer breakup for punchy, clear low frequencies.
- Centre Plug replaces traditional dust cap for cooler voice coil and higher power handling.

MIDRANGE AND TWEETER ATTENUATION SWITCHES

Cut high and mid frequencies on the fly with three-way attenuation switches (0, -3dB, -6dB) to custom tune the speaker to the listening space for smooth, detailed sound in any environment.

IMPEDANCE SELECTOR SWITCH

Custom tailor the speaker's impedance (4 ohm / 8 ohm) with the flip of a switch to optimize it to your amplifier or system.