

# IC 606 FGI

## 2-WAY IN-CEILING SPEAKER



### ALL NEW PURE WHITE GRILLE

Redesigned magnetic, paintable grille with a new, more natural white color blends more seamlessly into the most premium of interior décor.

### PREMIUM ACOUSTIC TECHNOLOGY

The 6.5" honeycomb fiberglass woofer and 1" silk dome pivot tweeter provide balanced, dynamic, rich sound for your music and movies by utilizing core Jamo technologies:

- Decoupled Tweeter Technology (DTT) minimizes vibration transfer from the baffle to the tweeter, for detailed, clear high frequencies.
- WaveGuide provides focused, dynamic transfer of high frequencies into the listening space.
- Hard Conical Cone (HCC) minimizes woofer breakup for punchy, clear low frequencies.
- Centre Plug replaces traditional dust cap for cooler voice coil and higher power handling.

### SPECIFICATIONS

WOOFER (mm / in)	165 / 6½
MIDRANGE (mm / in)	-
TWEETER (mm / in)	25 / 1 DTT
POWER (W LONG / SHORT TERM)	60 / 120
FREQUENCY RANGE (Hz)	65 – 22,000
IMPEDANCE (Ohm)	4 – 8 switchable
HOLE DIMENSION WxD (mm / in)	Ø201 x 99 / Ø7.9 x 4.0
DIMENSIONS WxD (mm / in)	Ø229 x 114 / Ø9.0 x 4.5
BACK BOX SIZE (Litre / in³)	14 / 850
WEIGHT	1.8 / 4.0
FINISH	White (paintable)

### PIVOT TWEETER

Aim the tweeter towards the listening space for maximum placement flexibility without sacrificing dynamic, detailed, on-axis high frequencies.

### TWEETER ATTENUATION SWITCH

Cut high frequencies on the fly with the three-way attenuation switch (0, -3dB, -6dB) to custom tune the speaker to the listening space for smooth, detailed sound in any environment.

### IMPEDANCE SELECTOR SWITCH

Custom tailor the speaker's impedance (4 ohm / 8 ohm) with the flip of a switch to optimize it to your amplifier or system.